



## Technical Datasheet Gerfix NDT Tape

### PRODUCT DESCRIPTION

A double-sided no down time (NDT) adhesive installation tape designed for use with Gerflor flooring.

### FEATURES AND BENEFITS

- Up to 98% RH / 15 MVER / pH 12
- No Down Time
- Quick installation

Technical Data	
Packaging	Box
Product	Tape (2.46' x 98.42') & perimeter tape (2" x 98.42')
Weight	18 lbs.
Coverage	250 sq ft
Color	silver
Open time	unlimited
Setting/Cure time	none
Minimum application temperature	65°F (18°C) and 65% RH (substrate level)
Foot traffic	immediate after installation
Welding / Joint sealing	immediate after installation
Shelf Life	12 months
Storage	Keep the box upright, in a dry, cool and protect from direct sunlight

### SUBSTRATE PREPARATION

The substrate must be sound, even, smooth, dry, and free of cracks, dust, residues, or any substances that could compromise adhesion performance.

If dust remains after cleaning, apply Gerfix NDT Primer to ensure the substrate is properly prepared and **dust-free** to ensure proper bonding.

### CRITICAL INSTALLATION POINTS

- Optimum conditions for product installation are 65-85°F (18-29°C) and relative humidity below 65%.
- Visit [gerflorusa.com](http://gerflorusa.com) for complete application instructions.



## Technical Datasheet Gerfix NDT Tape

### STORAGE

Store upright, dry, cool and out of direct sunlight.

### IMPORTANT NOTES

- Store upright, dry, cool and out of direct sunlight.
- Repack opened rolls in the cardboard box.
- Do not apply to wet surfaces.
- Substrate MUST be **free from dust**.
- **Do not install** if the concrete surface temperature is within 5°F of dew point.
- Use patching compounds rated equivalent to or greater than 98% RH.
- May be applied over radiated or thermally heated substrates, provided the substrate surface temperature does not exceed 85°F (29°C).

### CLEAN UP

Stack the release paper flat and then roll them up for disposal.

### SAFETY GUIDELINES

Consult and follow all Safety Data Sheet (SDS) instructions available at [www.GerflorUSA.com](http://www.GerflorUSA.com).

### WARRANTY

Gerflor warrants that this product has been manufactured from the highest quality raw materials, under conditions to meet rigid quality standards established by Gerflor. Therefore, the following is made in lieu of all other warranties expressed or implied. Sellers and manufacturers' sole obligation shall be to replace such quantity of the product proven to be defective. Neither seller nor manufacturer shall be liable for any loss or damage direct or consequential arising out of the use of or the inability to use this product. Before using, user shall determine the suitability of the product for his intended use. User assumes all risks and liability whatsoever in connection therewith. No person has authority to change these terms and there are no warranties, except as herein stated.

**For additional information, please contact Gerflor Customer Support at 1-877-437-3567.**

**Please refer to GerflorUSA.com for the latest installation instructions.**

**Gerflor USA, Inc.**  
750 Veterans Parkway  
Bolingbrook, IL 60440  
877-GER-FLOR (877-437-3567)GerflorUSA.com