

# Mural Club



B-s2,d0

PUR



100% recyclable\*



**0003 Sand** NCS : 1002-Y50R / LRV : 66.8



**0006 Grey** NCS : 1502-B / LRV : 60.9



**0001 White** NCS : 0500-N / LRV : 82.1



**0007 Blue** NCS : 1015-B / LRV : 63.1



**0004 Green** NCS : 1010-G / LRV : 69.3



**0005 Yellow** NCS : 1010-Y10R / LRV : 71.6

# Mural Club



## Technical performances

- Resistance to tearing
- Fire classification according to EN 13501: **B-s2,d0**



## Installation

- Horizontal or vertical installation (2 m width)
- Coloured backing for a perfect welding aspect
- A complete range of accessories for a durable and easy installation



## Aesthetics

- Slightly marbled design in 6 soft colours
- Colours matching the Gerflor ranges especially the Mipolam ranges



## Hygiene

- Smooth and washable surface
- No particle emission
- Reduces hospital acquired infections compliant with ISO 22196, inhibits growth of bacteria
- Good resistance to staining thanks to **PUR surface treatment**



## Eco-friendly

- Recyclable\*
- Contains recycled production wastes
- Raw materials 100% compliant with Reach
- Made in Europe

\*Via le Programme Seconde Vie

## Mural Club

Description / Beschreibung / Description / Beschrijving / Descripción / Descrição / Descrizione			
Total thickness / Gesamtdicke / Épaisseur totale / Totale dikte / Espesor total / Espessura total / Spessore totale	EN ISO 24346	mm	1.0
Thickness of wearlayer / Dicke Nutzschrift / Épaisseur couche d'usure / Dikte van de slijtlaag / Espesor capa de uso / Espessura camada de desgaste / Spessore strato di usura	EN ISO 24340	mm	1.0
Weight / Flächengewicht / Poids / Gewicht / Peso / Peso / Peso	EN ISO 23997	g/m <sup>2</sup>	1780
Width/length of sheet / Bahnenbreite/-länge / Largeur/longueur des lés / Rolbreedte/Rolengte / Ancho/largo de rollos / Largura/comprimento dos rolôs / Larghezza/lunghezza dei teili	EN ISO 24341	cm / ml	200 / 30
Phthalate free / Ftalatenvrij / Sans phtalates / Phthalatfrei / Sin ftalatos / Sem ftalatos / Senza ftalati	-	-	OK
Classification / Klassifizierung / Classification / Classificatie / Clasificaciones / Classificações / Classificazioni			
Norm/product specification / Produkt Norm / Norme produit / Technische eigenschappen / Normas / Normas / Norma prodotto	-	-	EN 259-1
Fire rating / Brandverhalten / Classement feu / Brand classificatie / Fuego / Fogo / Reazione al fuoco	EN 13 501-1	class	B-s2,d0
Performances / Technische Eigenschaften / Performances / Testresultaat / Cualidades Técnicas / Performances / Caratteristiche Tecniche			
Colour fastness / Lichtechtheit / Solidité lumière / Lichtechtheid / Resistencia a la luz / Estabilidade das cores / Solidità alla luce	EN ISO 105 - B02	degree	≥ 6
Surface treatment / Oberflächenvergrüfung / Traitement de surface / Oppervlaktebehandeling / Tratamiento de superficie / Tratamento de superfície / Trattamento di superficie	-	-	PUR
Chemical resistance / Verhalten gegenüber Chemikalien / Résistance aux produits chimiques / Chemische bestendigheid / Resistencia a los productos químicos / Resistência aos produtos químicos / Resistenza ai prodotti chimici	EN ISO 26987	-	OK
Environment / Milieu / Environnement / Umwelt / Medio ambiente / Ambiente / Ambiente			
Recycled content (average) / Gerecycled materiaal (gemiddeld) / Contenu recyclé (moyenne) / Anteil Recyclingmaterial (Durchschnitt) / Contenido reciclado (media) / Conteúdo reciclado (média) / Contenuto riciclato (medio)	-	%	18
Recyclability / Recycleerbaarheid / Recyclabilité / Wiederverwertbarkeit / Reciclabilidad / Reciclabilidade / Riciclabilità	-	%	100
Health / Santé / Gesundheit / Salud / Saúde / Salute			
Anti-bacterial activity / Antibacteriële werking / Activité anti-bactérienne / Antibacteriële activiteiten / Actividad antibacteriana / Atividade antibacteriana / Azione antibatterica <sup>(2)</sup>	ISO 22196	-	> 99% inhibits growth / > 99% Wachstumshemmend / > 99% ne favorise pas la prolifération / > 99% remt de groei van bacteriën / > 99% inhibe el crecimiento / > 99% inibe o desenvolvimento / > 99% inibisce la crescita
CE Marking / CE Kennzeichnung / Marquage CE / EG-Conformiteitsmerk / Marca de Conformidad CE / Marca de Conformidade CE / Marcatura CE Di Conformità			
	EN 15 102	-	OK

(1) The implementation of an effective cleaning method is the best defence against infection

(2) Anti-bacterial activity (E. coli - S. aureus MRSA) after 2h. The implementation of an effective cleaning regime is the most important defence against infection.

## We care / we act our commitments for 2030

<p><b>climate</b></p> <p><b>-30% CO<sub>2</sub></b> scopes 1, 2, 3 in tons eq. CO<sub>2</sub> vs 2019 Science Based Targets<sup>(1)</sup></p>	<p><b>resources</b></p> <p><b>75%</b> biobased, mineral and recycled content<sup>(2)</sup></p> <p><b>30%</b> recycled content<sup>(3)</sup></p>	<p><b>circularity</b></p> <p><b>65 000 tons</b> annual volume recycled<sup>(4)</sup></p> <p><b>45%</b> loose<sup>(5)</sup></p>	<p><b>health &amp; well-being</b></p> <p><b>100%</b> products better than Indoor Air Quality standards<sup>(6)</sup></p> <p><b>95%</b> sales covered by EPD<sup>(7)</sup></p>	<p><b>people</b></p> <p><b>30%</b> women<sup>(8)</sup></p> <p><b>40%</b> internal mobility<sup>(9)</sup></p> <p><b>Towards 0</b> accident<sup>(10)</sup></p>
---	---	--	---	--

**More details:** 1. Scopes 1, 2 & 3, in absolute value, market-based. Trajectory approved by SBTi (Science Based Targets Initiative). 2. Origin of raw materials for the entire Floor & Wall portfolio, on average, by weight; including 15% virgin salt, a primary element in vinyl manufacturing. Compared to 71% in 2024. 3. Average content in the Floor & Wall vinyl portfolio, by weight. Compared to 21% in 2024. 4. Recycled in our factories and recycling units. Compared to 59 040 tons in 2024. 5. % of Floor activity with non-glued products, easy to remove, easy to re-use. Compared to 40% in 2024. 6. 100% of vinyl and linoleum sold to the building market below 100 micrograms /m<sup>2</sup> (TVOC 28 days). 7. % of Floor & Wall activity covered by Environmental Product Declarations (EPD). Compared to 44% in 2024. 8. % women in our global workforce and among our managers. Compared to respectively 26% and 27% in 2024. 9. % job openings filled with internal hires worldwide. Compared to 25% in 2024. 10. Towards 0 accident: Lost time accident per million hours worked: below 3 vs 8,9 in 2024, for Gerflor employees worldwide.