

DESCRIPTION	STANDARDS	REQUIREMENTS	CREATION 70 CLIC		
PRODUCT DESCRIPTION					
Reference Specification*	ASTM F1700	-	Class III Type B		
Construction	-	-	Luxury Vinyl Tile		
Surface Treatment/Maintenance	-	-	ProtecShield™		
Gauge Total Thickness	ASTM F386	-	0.20" (5 mm)		
Wearlayer Thickness	ASTM F410	-	28 mil (0.7 mm)		
Backing	ASTM F1303	-	100% Recycled Material		
Plank & Tile Sizes	-	-	8.35" x 48.78"	9.45" x 57.52"	15.31" x 28.70"
Plank & Tile per Carton	-	-	7	6	6
Sq Ft Per Carton	-	-	19.8 ft ²	22.65 ft ²	18.31 ft ²
PERFORMANCE					
Dimensional Stability	ASTM F2199	-	Meets Requirements		
Indentation - Residual	ASTM F1914	≤ -8%	Meets Requirements		
Flexibility	ASTM F137	> 1"	Meets Requirements		
Size & Squareness	ASTM F2421	-	Meets Requirements		
Chemical & Stain Resistance	ASTM F925	-	Meets Requirements		
Resistance to Heat	ASTM F1514	ΔE ≤ 8	Meets Requirements		
Resistance to Light	ASTM F1515	ΔE ≤ 8	Meets Requirements		
Coefficient of Friction	ASTM D2047	-	0.67 (leather) / 0.80 (neolite)		
Impact Insulation (IIC)	ASTM E989 (ASTM E492)	-	IIC 46		
Fire Rating - Flame Spread	ASTM E648	Class 1	Meets Requirements		
ENVIRONMENT HEALTH & SAFETY					
Manufacturing Plant Certifications	ISO 9001, 14001, 50001	-	Quality, Environment, Energy		
Environmental Product Declaration (EPD)	LEED v5	-	Product-Specific Type III		
No Harmful Chemicals	LEED v5	-	100% REACH Compliant		
Sourcing of Raw Material: Recycled Content	Average Pre-Consumer Content	-	33%		
Indoor Air Quality / Low Emitting Materials	California Standard 01350	-	FloorScore® Certified		
Production Waste	LEED v5	-	100% Manufacturing Waste Recycled		
TVOC after 28 days	ISO 16000-6	-	<10µg/m ³		
WARRANTY	12-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions on gerflorusa.com				

*Rubber leaves indelible stains on synthetic floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.