

**DESCRIPTION 规格**

Total thickness 总厚度	ISO 24346 (EN 428)	mm	2
Width of sheet 卷宽	ISO 24341 (EN 426)	cm	200
Length of sheet 卷长	ISO 24341 (EN 426)	lm	20

**CLASSIFICATION 类别**

Norm / Product specification 产品规范	-	-	ISO 10581(EN 649)
European classification 产品分级	ISO 10874 (EN 685)	class	34 - 43
Fire rating 防火等级	EN 13 501-1	class	Bfl-s1
	GB 8624 - 2012	-	B <sub>1</sub> (B-s1,t0)
Toxic testing 有毒有害物质检测	GB 18586-2001	-	合格
Static electrical propensity 抗静电性	EN 1815	KV	≤ 2
Electrical resistance 抗电阻性	EN 1081	Ω	> 10 <sup>9</sup>
Slip resistance dry 防干滑性	EN 13893	-	≥ 0.3
Slip resistance wet 防湿滑性	DIN EN 16165	class	R9




**PERFORMANCES 性能**

Type binder content 粘合物分级	ISO 10581	type	I
Dimensional stability 尺寸稳定性	ISO 23999 (EN 434)	%	≤ 0.4
Castor chair test 椅子脚轮测试	ISO 4918 (EN 425)	-	OK
Thermal conductivity 热传导性	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness 颜色稳定性	ISO 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	ISO 26987 (EN 423)	-	OK
Special maintenance treatment 特殊维护处理	-	-	Evercare Elite 非凡丽
Anti-bacterial activity 抑菌性能 (E.coli - S.aureus 大肠杆菌和金黄色葡萄球菌) <sup>(1)</sup>	ISO 22196		抑菌率>99%
Antiviral activity (human coronavirus 229E) 抗病毒活性 (人类冠状病毒229E)	ISO 21702		99.7% (2小时)
Color number 颜色数量	-	-	50

**ENVIRONMENT / INDOOR AIR QUALITY 环保 / 室内空气质量**

TVOC after 28 days 28天后TVOC <sup>(2)</sup> 排放量	ISO 16000 - 6	µg/m <sup>3</sup>	< 10
Certification 证书	-	-	Floorscore®

**CE MARKING 标识**

	EN 14041	   
---	----------	---

Version no. CN2605

(1) The implementation of an effective cleaning regime is the most important defence against infections. 实施有效的清洁方法是抗感染最重要的防御措施。

(2) TVOC:挥发性有机化合物总排放量