

DESCRIPTION

Total thickness	ISO 24346 (EN 428)	mm	2
Weight	ISO 23997 (EN 430)	g/m ²	2950
Width of sheet	ISO 24341 (EN 426)	cm	200
Length of sheet	ISO 24341 (EN 426)	lm	20

CLASSIFICATION

Norm / Product specification	-	-	ISO 10581(EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13 501-1	class	Bfl-s1
	ASTM E648	class	Class I
Static electrical propensity	EN 1815	KV	≤2






PERFORMANCES

Type binder content	ISO 10581	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4
Residual indentation	ISO 24343-1 (EN 433)	mm	≤ 0.1
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	Not affected ⁽¹⁾
Surface treatment	-	-	PUR+
Anti-bacterial activity (E. coli - MRSA) ⁽²⁾	ISO 22196		>99% Inhibits growth
Color number	-	-	26

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000 - 6	µg/m ³	<10
Certification	-	-	Floorscore®

CE MARKING

	EN 14041	   
---	----------	---

(1) Regarding the resistance to chemicals, please refer to the reports.

(2) The implementation of an effective cleaning regime is the most important defence against infections.