




**POWERSHOCK**  
RUBBER SOLUTIONS FOR FITNESS

**Gerflor**<sup>®</sup>

# POWERSHOCK 300

## CROSSFIT & HEAVY-WEIGHT AREA



30mm  
TILES WITH PRE-INSTALLED  
CONNECTOR PINS



### Outstanding protection of floor and fitness equipment:


- ✓ High shock absorption and sound insulation
- ✓ Great protection of the subfloor: withstands weights up to 200kg dropped from a 2m height
- ✓ Non-glued, easy to install tiles with connector pins




DARK GREY



### ACCESSORIES



Ramp edge rubber - 30mm  
1m



Corner ramp edge rubber - 30mm  
2 units (1000 x 250mm)

# POWERSHOCK



Y1000299

## POWERSHOCK

300

CROSSFIT &  
HEAVY-WEIGHT AREA

## DESCRIPTION

Thickness	NF EN ISO 24346	mm	30 (± 2)
Weight	NF EN ISO 23997	kg/tile	6.8 (± 0.2)
Size	NF EN ISO 24342	mm	500 x 500 (± 0.8%)

## CLASSIFICATION

Fire resistance	EN 13501-1	class	C <sub>fl</sub> ,s1
VOC	ISO 16000-6	class	A+

## PERFORMANCE

Dimensional stability	NF EN ISO 23999	%	< 0.1
Abrasion	EN ISO 5470-1	g	1.5
Light resistance	EN ISO 20105 - B02	level	3
Indentation resistance	EN 1516	mm	0.12
Slip resistance in dry condition	EN 13036-4	unit	80-110
Sound insulation	EN ISO 717/2	dB	24
Hardness shore A	Int.	-	60

### WE CARE | WE ACT our commitments for 2030

 <b>climate</b> -30% CO2 scopes 1,2,3 in tons eq CO2 vs 2019 <small>Science Based Targets</small>	 <b>recources</b> 75% biobased, mineral, recycled content 30% recycled content	 <b>circularity</b> 65,000 tons of waste recycled 45% looselay	 <b>health &amp; well-being</b> 100% outperforming Indoor Air Quality standards 95% sales covered by EPDs	 <b>people</b> Towards 0 accidents 30% women 40% internal mobility
--	---	---	--	--

\*for further information please visit our website [www.gerflor.com](http://www.gerflor.com)

**Be connected!**

[www.gerflor.com](http://www.gerflor.com)

**#Gerflor**

#### FRANCE:

Gerflor - ServiceExpress

**N°Azur 0 810 569 569** **N°Azur FAX 0 810 569 570**

e-mail: [contactfrance@gerflor.com](mailto:contactfrance@gerflor.com)

#### OTHER COUNTRIES:

Gerflor International

Tel: +33(0)474054000 - Fax: +33(0)474050313

e-mail: [gerflorcontract@gerflor.com](mailto:gerflorcontract@gerflor.com)

