



## **Taraflex® Bateco**

Moveable protective layer

**Gerflor®**



# Protect your sport hall for extra sport use

Taraflex® Bateco is the ideal moveable solution for protecting sport floors during non-sporting activities. It can be unrolled over floors and then rolled up again before resuming sports activities.



Efficient protection of the sport flooring



Sustainable protective solution



Easy to install and to remove for multiple uses



Specific range of equipment available

BATECO INSTALLED ON HARDWOOD SUBFLOOR



Made of 80% post-manufacturing waste



100% recyclable



Antibacterial environments



TVOC emissions below detection level  
(TVOC <100µg/m3 after 28 days)

# Taraflex® Bateco Moveable protective layer



1 Special protective grain  
Black: masking sober



Thin layer with special protective grain prevents marks and stains, easy maintenance



Customizable length every 0,5 lm from 12 lm to 45 lm  
Width: 1,5 m



Outstanding fire resistance  
Bfl-S1



Looselay and edge-to-edge installation: can be secured with single-sided tape adhesive

## WIDE RANGE OF ACCESSORIES TO EASE THE INSTALLATION

MOBILE OR STATIC  
STORAGE RACKS



SINGLE-SIDED TAPE AND  
UNROLLER



SERVING TROLLEYS



| DESCRIPTION                                                                        | STANDARD                 | REQUIREMENT | UNITS             | TARAFLEX® BATECO       |
|------------------------------------------------------------------------------------|--------------------------|-------------|-------------------|------------------------|
| PRODUCT DESCRIPTION                                                                |                          |             |                   |                        |
| Surface treatment                                                                  |                          |             |                   |                        |
| Surface complex                                                                    |                          |             |                   |                        |
| Foam                                                                               |                          |             |                   |                        |
| Thickness                                                                          | EN ISO 24346<br>(EN 428) |             | mm                | 1,5                    |
| Weight                                                                             | EN ISO 23997<br>(EN 430) |             | kg/m <sup>2</sup> | 2,5                    |
| Length                                                                             | EN ISO 24341<br>(EN 426) |             | ml                | 45 Max                 |
| Width                                                                              | EN ISO 24341<br>(EN 426) |             | ml                | 1,5                    |
| TECHNICAL CHARACTERISTICS                                                          |                          |             |                   |                        |
| Abrasion resistance                                                                | EN ISO 5470-1            | ≤ 1000      | mg                | ≤ 300                  |
| Impact resistance                                                                  | EN 1517                  | ≥ 8         | N/m               |                        |
| Indentation resistance                                                             | EN 1516                  | ≤ 0,5       | mm                | ≤ 0,5                  |
| Dimensional stability                                                              | EN ISO 23999             |             | %                 | 1                      |
| CLASSIFICATION                                                                     |                          |             |                   |                        |
| Fire                                                                               | EN 13501-1               |             |                   | Bfl-s1                 |
| Anti-bacterial activity (E. coli - S. aureus - MRSA) <sup>(1)</sup>                | ISO 22196                |             |                   | > 99 % inhibits growth |
| CE MARKING                                                                         |                          |             |                   |                        |
|  | EN 14041                 |             |                   | Fire                   |
| INSTALLATION METHODS                                                               |                          |             |                   |                        |
|                                                                                    | GERFLOR'S RECOMMENDATION |             | UNITS             | RESULTS                |
| LOOSE LAY ON THE EXISTING FLOORING                                                 |                          |             |                   |                        |

(1) The implementation of an effective cleaning method id the best defence against infection

we care / we act our commitments for 2030

|                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                            |                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>climate</b><br><br><b>-30% CO<sub>2</sub></b><br>scopes 1, 2, 3<br>in tons eq. CO <sub>2</sub> vs 2019<br>Science Based Targets <sup>(1)</sup> | <br><b>resources</b><br><br><b>75%</b><br>biobased, mineral<br>and recycled content <sup>(2)</sup><br><br><b>30%</b><br>recycled content <sup>(3)</sup> | <br><b>circularity</b><br><br><b>65 000 tons</b><br>annual volume recycled <sup>(4)</sup><br><br><b>45%</b><br>looselay <sup>(5)</sup> | <br><b>health &amp; well-being</b><br><br><b>100%</b><br>products better than<br>Indoor Air Quality<br>standards <sup>(6)</sup><br><br><b>95%</b><br>sales covered by EPD <sup>(7)</sup> | <br><b>people</b><br><br><b>30%</b><br>women <sup>(8)</sup><br><br><b>40%</b><br>internal mobility <sup>(9)</sup><br><br><b>Towards 0</b><br>accident <sup>(10)</sup> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

More details: 1. Scopes 1, 2 & 3, in absolute value, market-based. Trajectory approved by SBTi (Science Based Targets Initiative). 2. Origin of raw materials for the entire Floor & Wall portfolio, on average, by weight; including 15% virgin salt, a primary element in vinyl manufacturing. Compared to 71% in 2024. 3. Average content in the Floor & Wall vinyl portfolio, by weight. Compared to 21% in 2024. 4. Recycled in our factories and recycling units. Compared to 59 040 tons in 2024. 5. % of Floor activity with non-glued products, easy to remove, easy to re-use. Compared to 40% in 2024. 6. 100% of vinyl and linoleum sold to the building market below 100 micrograms /m³ (TVOC 28 days). 7. % of Floor & Wall activity covered by Environmental Product Declarations (EPD). Compared to 44% in 2024. 8. % women in our global workforce and among our managers. Compared to respectively 26% and 27% in 2024. 9. % job openings filled with internal hires worldwide. Compared to 25% in 2024. 10. Towards 0 accident: Lost time accident per million hours worked: below 3 vs 8,9 in 2024, for Gerflor employees worldwide.

