

DESCRIPTION

Total thickness	EN ISO 24346	mm	6,00
Thickness of wear layer	EN ISO 24340	mm	2
Weight	EN ISO 23997	g/m ²	9 365
Tile size	EN ISO 24342	mm	neoConnect : 640 x 640 Cleantech : 600 x 600

CLASSIFICATION

Norm / Product specification	-	-	EN ISO 10582
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	B _{fl} -s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet : ramp test with oil	EN 16165 app. B (DIN 51130)	class	R10

PERFORMANCE

Wear resistance	EN 660.2	mm ³	< 2
Wear group	-	group	T
Type Binder content	EN ISO 10582	type	I
Dimensional stability (norm) (measured value)	EN ISO 23999	%	≤ 0,15 (≤ 0,10)
Residual indentation	EN ISO 24343-1	mm	≤ 0,10
Castor chair test (type H)	ISO 4918	-	OK
Shore hardness	EN ISO 868	H _D	≥ 50
Shifting resistance	CAHIER CSTB 3562	N/mm ²	≥ 30
Thermal conductivity	EN ISO 10456	W/(m.K)	0,25
Color fastness	ISO 105 - B02	degree	≥ 6
Impact sound insulation	EN ISO 717-2	dB	6
Walking noise	NF S31-074	dB	79 (Class C)
Surface treatment	-	-	PUR+
Chemical products resistance	EN ISO 26987	-	OK

ENVIRONMENT / INDOOR AIR QUALITY

Recycled content			50%
Recyclability			Yes
EPD / FDES			Yes / Yes
TVOC after 28 days	ISO 16000-6	µg/m ³	< 10
Certification	-	-	Floorscore®

CE MARKING



EN 14041

-

