

TECHNICAL DATA SHEET

KENBROCK SMARTDROP ULTIMATE

KENBROCK SMARTDROP ULTIMATE

Description

Total thickness	ISO 24346 (EN 428)	mm	5.00
Thickness of wearlayer	ISO 24340 (EN 429)	mm	0.55
Weight	ISO 23997 (EN 430)	g/m ²	9020
Plank format	ISO 24342 (EN 427)	mm	230 × 1500
Product per carton		tiles / m ²	5 / 1.725
Product per pallet		boxes / m ²	54 / 93.15
Colour references			12

Classification

Norm/Product Specification			EN653
European Classification	ISO 10874 (EN 685)	class	33-42
Fire rating	AS 5637.1-2015	kW / m ²	9.4
		M ² /kg	215
Static electrical propensity	EN 1815	kV	≤ 2
Slip rating oil wet-ramp	AS 4586 2013 (Appendix D)	class	R10
Slip rating oil wet pendulum	AS 4586 2013 (Appendix A)	class	P3

Performance

Wear Group	EN 649	-	T
Dimensional stability	ISO 23999 (EN 434)	%	0.20
Residual indentation	ISO 24343-1 (EN 433)	mm	0.05
Impact sound insulation	AS ISO 717-2-2004	LnTw	50
Colour fastness	ISO 105 - B02	degree	≥ 6
Surface treatment	-	-	PUR+

Environment / Indoor Air Quality

TVOC	ASTM D5116:2017	mg/m ² /hr	0.035
Resilooop			Yes

(1) The implementation of an effective cleaning regime is the most important defence against infections.